

# Oasis Irrigation Equipment Co Ltd.

P-6, Scheme-VI M(S) C.I.T Kolkata-700 054, Ph: 033-2364-8812

Email: [info@oasisirrigation.in](mailto:info@oasisirrigation.in)

Website: [www.oasisirrigation.in](http://www.oasisirrigation.in)



## **Impact Type Pop Up Sprinklers**

Oasis  $\frac{3}{4}$ " BSP Female Thread Connection ( $\frac{1}{2}$ " BSP Female Thread Connection on side) Salient Features:

- Straight Flow for Dirty Water Application
- Proven Impact Drive
- Spacing up to 45 feet (13.7 m)
- Heavy Duty plastic case worth sturdy reinforced ribbed design
- Double weighted arm for slower rotation and increased distance of throw
- Self flushing inner trip with improved inner trip lever
- Powerful reverse action
- Adjustable arm spring for low pressure and low gallonage operating
- Energy efficient, low pressure
- Full Circle or adjustable arc 20°-340°
- Hooded bearing
- Distance controller diffused pin
- Multi function, pressure activated wiper seal

- Inner filter screen
- Serviceable through the top of the case
- Combination of ½" or ¾" connection

**Operating Range:**

- Precipitation rate: 5.8 to 26.6 mm/hr)
- Spacing: 6.7 to 13.7 m
- Flow rate: 0.01 to 0.52 lps
- Radius: 6.7 to 13.7 m
- Pressure: 2 to 4.5 bars